Platinum ECO SN/CF, C3

SAE 5W-30 / 5W-40

PASSENGER CAR

About

SYNERGY PLATINUM ECO C3 utilizes a fully synthetic formulation to give extra engine performance and fuel economy.

Meeting a myriad of car manufacturer standards, it is designed specifically for European vehicles, and is especially suitable for cars fitted with turbocharged engines with Exhaust Gast Recirculation (EGR), and Diesel Particulate Filter (DPF).

Properties & Characteristics (Typical Values)

	Unit	5W-30	5W-40
Density @ 15°C	kg/l	0.8504	0.8507
Kinematic Viscosity @ 100°C	cSt	12.06	14.68
Kinematic Viscosity @ 40°C	cSt	69.25	86.15
Viscosity Index	-	173	179
Pour Point	°C	-39	-39
Flash Point COC	°C	216	216

Product Benefits

- Fuel economy
- Engine power and maintainability
- Longer oil drainage intervals
- All-temperature wear resistance

Specifications

Synergy Platinum ECO 5W30 and 5W40 meets or exceeds the following services and specifications:

- ACEA C3
- API SN/SM/SL/CF
- MB-Approval 229.31/229.51
- BMW Longlife - 04
- GM dexos 2
- Renault RN0700/RN0710
- MB-Approval 226.5
- Porsche A40 (only for SAE 5W-40 viscosity grade)
- VW 505 00/505 01 (only for SAE 5W-40 viscosity grade)